

## Round tapered flag poles

MOUNTING HEIGHTS FROM 20' TO 50'

Round, smooth tapered aluminum shaft, 6063-T6 alloy. Mounting heights from 20' to 50'. Poles and brackets are rotary sanded. Standard thermoset polyester power coating is available in the following colors: Black, Black Sandtex, Hammetone Black, Bronze and Fence Green. Other colors are available on request. Contact our sales staff for complete details and pricing. Optional components, such as ladder rests, flag holders, banner arms and alternative bolt circles are available on request.

Cast aluminum revolving truck.

Standard cast aluminum base, 356-T6 alloy, for foundation mounting.



For foundation mounting, anchor bolts are 3/4" diameter x 24" long for 20' poles, 1" x 36" for 25' to 35' poles, and 1-1/4" x 40" for 40' to 50' poles, with hex nut, lockwasher and flatwasher (four of each required). Anchor bolt as per ASTM A576 steel with 50,000 PSI yield strength. Top 12" of bolt to be galvanized as per ASTM A153. Direct burial poles are alkali-resistant coal tar epoxy coated or alternatively, Thermoset Polyester Powder Coated, inside and out, and wrapped with rubber.

### Internal Halyard Options:

- Stainless steel external cable.
- Stainless steel flag arrangement.
- Retainer ring with 1" nylon balls.
- Ball Top, Cone Top, Eagle or Maple Leaf.
- Stainless steel winch.
- Flush mounted access door with security screws.

### External Halyard Options:

- Nylon rope.
- Stainless steel flag arrangement.
- Ball Top, Cone Top, Eagle or Maple Leaf.
- Cast aluminum cleat.



Direct Burial Pole Available



CATATOG NUMBER	HEIGHT (FEET)	BASE DIAMETER (INCHES)	TOP DIAMETER (INCHES)	WALL THICKNESS (INCHES)	NUMBER OF SECTIONS	FLAG SIZE (FEET)
USS4030A20AB-FLG	20'	4"	3"	0,125"	1	4x6'
USS5030C20AB-FLG	20'	5"	3"	0,188"	1	4x6'
USS5030C25AB-FLG	25'	5"	3"	0,188"	1	4x6'
USS5030C30AB-FLG	30'	5"	3"	0,188"	1	5x8'
USS6035C35AB-FLG	35'	6"	3-1/2"	0,188"	1	5x8'
USS7035C40AB-FLG	40'	7"	3-1/2"	0,188"	2	6x10'
USS8040C45AB-FLG	45'	8"	4"	0,188"	2	6x10'
USS1040C50AB-FLG	50'	10"	4"	0,188"	2	6x10'

### Notes:

Direct burial depth is minimum 4'-0". Other options are available upon request.

### Two revolving truck models are available:

- Standard Model - #TRK-9680
- Heavy Duty Model - #TRK-9660

### Three sizes of counterweights are available:

- 3-1/2" - Model #CWA-9100
- 7" - Model #CWA-9200
- 14" - Model #CWA-9300

Contact our Sales Staff for additional options.